



mt-propeller



Type of Aircraft: Aerostar PA-60
FAA STC #: SA01511SE
EASA/LBA STC #: SA1403
Aircraft TCDS #: A17WE
Propeller TCDS #: P3BO

Applicable Aircraft

PA-60-600, -601, -601P, -602P

Engines

Lycoming
 IO-540-S1A5-MM, IO-540-AA1A5-MM,
 (L)TIO-540-U2A



STC Kit Contents

Two 4-Blade Full Feathering Constant Speed Propellers	MTV-14-B-C-F/CF(L)188-30d
Two Full Composite Spinner (AFRP)	P-587
One Airplane Flight Manual Supplement	Doc. No. E-1106 or E-1107
One Installation Instruction	Doc. No. E-1108
One Operation and Installation Manual	ATA 61-01-24 (E-124)

Propeller Specifications

Full Propeller Designation	MTV-14-B-C-F/CF(L)188-30d
Propeller Hub	MTV-14-B-C-F
Blade	Milled single-piece aluminum hub
Blade Design	CF188-30d, CFL188-30d
Installed Propeller & Spinner Weight	Light-weight natural composite
Maximum Diameter	73.4 lbs each
Minimum Diameter	74 in.
TBO	72 in.
	1800 hrs / 72 month (whichever occurs first)

Options

HiGlo® Full Composite Spinner (AFRP) with chrome finish

Replaces

3-Blade Hartzell HC-C3YR-2/C8468-8R, HC-CYR-2UF/FC8468-8R
 3-Blade Hartzell HC-C3YR-2UF/FC8468DB-14
 3-Blade Hartzell HC-C3YR-2UF/FC8468DB-14(MM)

Advantages

- Best vibration dampening characteristics for almost vibration free propeller operations
- Bonded on stainless steel leading edge for best erosion protection of the blades
- Shorter take-off distance remains unchanged
- Enhanced climb by approx. 3% to 5% (SL, ISA conditions)
- Cruise performance increased by approx. 3 to 5 kts (MTOW, ISA conditions)
- Approx. 40 lbs less weight than the original propellers
- Unlimited blade life
- No airframe resonance with low engine rpm
- Significant inside and outside noise reductions

MT-Propeller Entwicklung GmbH
 Flugplatzstr. 1
 94348 Atting / Germany

Phone: +49 (0) 9429 9409 0
 Fax: +49 (0) 9429 8432
 sales@mt-propeller.com

MT-Propeller USA, Inc.
 1180 Airport Terminal Drive
 DeLand, Florida 32724

Phone: (386) 736-7762
 Fax: (386) 736-7696
 info@mt-propellerusa.com